

CARTRIDGE HEATERS STOCK PROGRAM

LAGERPROGRAMM HEIZPATRONEN

Cartridge Heaters Heizpatronen

	PE	PDE	PDS	PDZ	PDH	PZH	HPS	HPZ	O
operating temperature¹⁾ Einsatztemperatur ¹⁾	400 °C	500 °C	750 °C	750 °C	750 °C	750 °C	750 °C	750 °C	600 °C
max load max. Leistungsdichte	4 W/cm ²	10 W/cm ²	15 W/cm ²	15 W/cm ²	20 W/cm ²	20 W/cm ²	30 W/cm ²	30 W/cm ²	4 W/cm ²
scale unit Masseinheit	mm	mm	mm	inch Zoll	mm	inch Zoll	mm	inch Zoll	mm

¹⁾ **max at cartridge surface / max. am Patronenmantel**
for further information please see as well technical data
 weitere Informationen entnehmen Sie bitte den Technischen Daten

Watt	Cartridge length in mm / Patronenlänge in mm												
	50	60	80	100	130	150	160	180	200	225	250	275	300
Ø													
6.5 mm PDS	on request / auf Anfrage	100	100	100	220	350							
		125	125	160	300	400							
		150	150	200	350								
		160	160	220	390								
		180	250	300									
		200	300										
8.0 mm PDE		125	160	180	250		200						
		140	200	200	315								
		150		250									
		160											
8.0 mm PDS	140	125	160	180	250	410	200						
	160	140	200	200	315	500							
		150	220	250	350								
		160	250	280	400								
		180		315									
		200		370									
8.0 mm PDH				350	450		500						
				400	500		600						
10.0 mm PDE	100	125	100	125	250	210	200		290	300	370	410	450
	160	140	160	135	315	340	400		300	525	400	650	500
		150	200	180	400		500		400	670	590		710
		160	220	200					465		630		
		180	250	210					600		700		
		200		220					630		800		
				250									
				280									
				315									
				350									
				400									
				520									
10.0 mm PDS	100	125	100	125	250	210	200	650	290	300	370	410	450
	160	140	160	135	315	340	400	700	300	525	400	650	500
	170	150	200	180	400	550	500	820	400	670	590		710
	200	160	220	200	450	600	630		465	800	630		
	230	180	250	210	500	700	700		600	900	700		
		200	300	220	580				630	1050	800		
		220	315	250					700		900		
		260	370	280					820		1000		
		300		315							1150		
				350									
				400									
				520									

Subject to change and prior sale / Änderungen + Zwischenverkauf vorbehalten



CARTRIDGE HEATERS STOCK PROGRAM

LAGERPROGRAMM HEIZPATRONEN

Watt	Cartridge length in mm / Patronenlänge in mm												
Ø	50	60	80	100	130	150	160	180	200	225	250	275	300
10.0 mm PDH					750		800 900	850 900	800 1000				
12.5 mm PDE	100 160 200	125 160 200 250	120 150 195 200 250 300 315	160 200 250 315 400	250 400 500	255 405	300 500 600 630	670	350 400 555 630 700	395 630	440 705 800 900	490 780	535 600 860
12.5 mm PDS	100 160 200 220 250 300	125 160 200 250 280 330 380	120 150 195 200 250 300 315 400 430 470	160 200 250 315 400 430 510 600	250 400 500 650 750 880	255 405 650 750 880	300 500 600 630 700 800 880	670 800 900 1050	350 400 555 630 700 900 1000 1020	395 630 1000 1150 1300	440 705 800 900 1100 1250 1450	490 780 1200 1400 1600	535 600 860 1400 1750
12.5 mm PDH			500 630		1000		1000 1250	1000 1400	800 1500		1000 1250		1500 2000
16.0 mm PDE	160 200 250	160 200 250 315	180 200 280 315 400	230 300 350 360 400 500	400 500 630	350 560	500 630 700 800	850	480 500 600 760 800 1000	540 860	600 700 960 1000 1250	670 1060	730 1000 1250 1500
16.0 mm PDS	160 200 250 270 315 380	160 200 250 315 360 420 490	180 200 280 315 400 450 500	230 300 350 360 400 500 600 700 750	400 500 630 700 800 940	350 560 850 1000 1100	500 630 700 800 900 1000 1100	850 1000 1250 1300	480 500 600 760 800 1000 1100 1250 1500	540 860 1300 1450 1650	600 700 960 1000 1250 1400 1600 1875	670 1060 1600 1800 2050	730 1000 1160 1250 1500 1800 2000 2250
16.0 mm PDH			800	1000			1600	1800	2000		2000		2000
20.0 mm PDS	380 420 470	450 510 570	600 680 750	800 850 900	900 1100 1200	1000 1250 1400	1000 1250 1500	1350 1500 1650	1500 1600 1800	1650 1900 2100	1900 2300	2050 2300 2500	2250 2600
20.0 mm PDH	315 400	630	1000	1400	1800		1800	1900	2000 2500		2000 2500		2200 2500

Subject to change and prior sale / Änderungen + Zwischenverkauf vorbehalten

